



Environmental

PH#: 941-747-4151

4455 18th St. East, Bradenton, FL 34203

barriers@aerflo.com

Universal 10-Gallon Spill Kit - Absorbs up to 9.5 Gallons

SPKU-10 Specifications

| | |
|------------------------|---|
| Dimensions: | ext. dia. 15" x 18.3" H |
| Shipping | 18" W x 18" L x 20" H |
| Dimensions: | |
| Sold as: | 1 per package |
| Absorbency per: | Up to 9.5 gal. |
| Weight: | 16.65 lbs. |
| # per Pallet: | 30 |
| Incinerable: | No |
| Ship Class: | 175 |
| Includes: | 20 - 15" X 19" Gray Universal Defender Pads (GPB100H) 3 - 3" X 4' Gray Universal Sorbent Socks (GSO430) 1 - 8" X 18" Gray Universal Sorbent Pillow (GPIL818) 2 - 18" X 6" X 30" Yellow Disposal Bags & Ties (A-DISP BAG-SM) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" X 5" Vinyl Spill Kit Label (A-KIT LABEL) 1 - 15" X 18.3" Yellow 10 Gallon Drum (A10DRUM) 1 - 6" X 2" TamperProof Seals (A-SEAL) |



Metric Equivalent Specifications

| | |
|------------------------|--------------------------|
| Dimensions: | ext. dia. 38cm x 46cm H |
| Shipping | 46cm W x 46cm L x 51cm H |
| Dimensions: | |
| Absorbency per: | Up to 36 L |
| Weight: | 7.6 kg |

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."