



Environmental

PH#: 941-747-4151

4455 18th St. East, Bradenton, FL 34203

barriers@aerflo.com

Universal 55-Gallon Spill Kit - Absorbs up to 48.9 Gallons

SPKHZ-55 Specifications

Dimensions:	ext. dia. 24" x 40" L
Shipping	24" W x 40" L x 24" H
Dimensions:	
Sold as:	1 per package
Absorbency:	Up to 48.9 gal. per package
Weight:	55.39 lbs.
# per Pallet:	8
Incinerable:	No
Ship Class:	175
Includes:	100 - 15" x 19" Yellow HazMat HeavyWeight SonicBonded Pads (YPB100H) 10 - 3" x 4' Yellow HazMat Sorbent Socks (YSO430) 5 - 18" x 18" Yellow HazMat Sorbent Pillows (YPIL1818) 2 - Pair Nitrile Gloves (A-GLV-NIT) 2 - Pair Goggles (A-GOG) 1 - Emergency Guide Book (A-EGB) 4 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISPAG) 6 - 6" x 2" Tamper Proof Seals (A- SEAL) 1 - 24" X 40" Yellow 55-Gallon Drum (1H2/X100/S) (A55DRUM)



Metric Equivalent Specifications

Dimensions:	ext. dia. 61cm x 102cm L
Shipping	61cm W x 102cm L x 61cm H
Dimensions:	
Absorbency:	Up to 185.1 L per package
Weight:	25.1 kg

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."