



Environmental

PH#: 941-747-4151

4455 18th St. East, Bradenton, FL 34203

barriers@aerflo.com

HazMat 5-Gallon Spill Kit - Absorbs up to 4.6 Gallons

SPKHZ-5 Specifications

Dimensions:	ext. dia. 12" x 16.75" H
Shipping	13.4" W x 13.4" L x 17.25" H
Dimensions:	
Sold as:	1 per package
Absorbency:	Up to 4.6 gal. per package
Weight:	13.05 lbs.
# per Pallet:	24
Incinerable:	No
Ship Class:	175
Includes:	10 - 15" x 19" Yellow HazMat HeavyWeight SonicBonded Pads (YPB100H) 2 - 3" x 4' Yellow HazMat Sorbent Socks (YSO430) 2 - 18" x 30" Yellow Disposal Bag & Tie (A-DISPAG-SM) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A- KITLABEL) 1 - 12" x 16.75" White 5-Gallon OverPack (1H2/Y1.5/30) (A5OVER) 1 - 6" x 2" TamperProof Seals (A- SEAL)



Metric Equivalent Specifications

Dimensions:	ext. dia. 30cm x 43cm H
Shipping	34cm W x 34cm L x 44cm H
Dimensions:	
Absorbency:	Up to 17.4 L per package
Weight:	5 kg

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."