



PH#: 941-747-4151

4455 18th St. East, Bradenton, FL 34203

barriers@aerflo.com

Oil-Only 65-Gallon Spill Kit # - Absorbs up to 43.8 Gallons

SPKO-65 Specifications

Dimensions:	ext. dia. 28.25" x 37.37" H
Shipping Dimensions:	28.25" W x 37.37" L x 28.25" H
Sold as:	1 per package
Absorbency:	Up to 43.8 gal. per package
Weight:	81.52 lbs.
# per Pallet:	2
Incinerable:	No
Ship Class:	175
Includes:	40 - 15" x 19" White Oil-Only HeavyWeight SonicBonded Pads (WPB100H) 10 - 3" x 4' White Oil-Only Sorbent Socks (WSO430) 6 - 3" x 8' White Oil-Only Sorbent Socks (WSO815) 6 - 18" x 18" White Oil-Only Sorbent Pillows (WPIL1818) 2 - Pair Nitrile Gloves (A-GLV-NIT) 3 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISP BAG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KIT LABEL) 1 - 28.25" x 37.37" Yellow 65-Gallon OverPack (1H2/X200/S) (A65OVER) 1 - Safety Goggles (A-GOG) 6 - 6" x 2" TamperProof Seals (A-SEAL) 1 - Emergency Response GuideBook (A-EGB)



Metric Equivalent Specifications

Dimensions:	ext. dia. 72cm x 95cm H
Shipping Dimensions:	72cm W x 95cm L x 72cm H
Absorbency:	Up to 165.8 L per package
Weight:	37 kg

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."