



**PH#: 941-747-4151**

**4455 18<sup>th</sup> St. East, Bradenton, FL 34203**

**barriers@aerflo.com**

## **Oil-Only 95-Gallon Spill Kit # - Absorbs up to 79.7 Gallons**

### **SPKO-95 Specifications**

|                      |  |
|----------------------|--|
| <b>Dimensions:</b>   | ext. dia. 31.75" x 41.5" H   |
| <b>Shipping</b>      | 31.75" W x 41.5" L x 31.75" H  |
| <b>Dimensions:</b>   |  |
| <b>Sold as:</b>      | 1 per package  |
| <b>Absorbency:</b>   | Up to 79.7 gal. per package  |
| <b>Weight:</b>       | 105.4 lbs.   |
| <b># per Pallet:</b> | 2  |
| <b>Incinerable:</b>  | No   |
| <b>Ship Class:</b>   | 175  |
| <b>Includes:</b>     | 150 - 15" x 19" White Oil-Only HeavyWeight<br>SonicBonded Pads<br>(WPB100H)<br>12 - 3" x 4' White Oil-Only Sorbent Socks<br>(WSO430)<br>6 - 3" x 8' White Oil-Only Sorbent Socks<br>(WSO815)<br>7 - 18" x 18" White Oil-Only Sorbent Pillows<br>(WPIL1818)<br>3 - 1 lb. Plug & Dike Epoxy Putty (A-PND)<br>2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety<br>Goggles (A-GOG)<br>4 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-<br>DISPBAG)<br>1 - Emergency Response GuideBook (A-EGB)<br>1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL)<br>1 - 31.75" x 41.5" Yellow 95-Gallon OverPack<br>(1H2/X295/S) (A95OVER) 6 - 6" x 2"<br>TamperProof Seals (A-SEAL) |



### **Metric Equivalent Specifications**

|                    |                           |
|--------------------|---------------------------|
| <b>Dimensions:</b> | ext. dia. 81cm x 105cm H  |
| <b>Shipping</b>    | 81cm W x 105cm L x 81cm H |
| <b>Dimensions:</b> |                           |
| <b>Absorbency:</b> | Up to 301.7 L per package |
| <b>Weight:</b>     | 47.8 kg                   |

### **Regulations and Compliance:**

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."