



Environmental

PH#: 941-747-4151

4455 18th St. East, Bradenton, FL 34203

barriers@aerflo.com

Oil-Only 95-Gallon Wheeled Spill Kit - Absorbs up to 79.7 Gallons

SPKO-95-WD Specifications

Dimensions:	ext. dia. 36" x 47" H
Shipping Dimensions:	36" W x 47" L x 36" H
Sold as:	1 per package
Absorbency:	Up to 79.7 gal. per package
Weight:	113.4 lbs.
# per Pallet:	1
Incinerable:	No
Ship Class:	250
Includes:	150 - 15" x 19" White Oil-Only HeavyWeight SonicBonded Pads (WPB100H) 12 - 3" x 4' White Oil-Only Sorbent Socks (WSO430) 6 - 3" x 8' White Oil-Only Sorbent Socks (WSO815) 7 - 18" x 18" White Oil-Only Sorbent Pillows (WPIL1818) 3 - 1 lb. Plug & Dike Epoxy Putty (A-PND) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 4 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISP BAG) 1 - Emergency Response GuideBook (A-EGB) 1 - 3" x 5" Vinyl Spill Kit Label (A-KIT LABEL) 1 - 32" dia x 47" Yellow 95-Gallon Wheeled OverPack (1H2/X113/S) (A95OVER-WD) 6 - 6" x 2" TamperProof Seals (A-SEAL)



Metric Equivalent Specifications

Dimensions:	ext. dia. 91cm x 119cm H
Shipping Dimensions:	91cm W x 119cm L x 91cm H
Absorbency:	Up to 301.7 L per package
Weight:	51.4 kg

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."