



*Environmental*

**PH#: 941-747-4151**

**4455 18<sup>th</sup> St. East, Bradenton, FL 34203**

**barriers@aerflo.com**

## **Universal Cart 5in Wheeled Spill Kit - Absorbs up to 109.9 Gallons**

### **SPKU-CART5 Specifications**

<b>Dimensions:</b>	31" W x 48" L x 38" H
<b>Shipping Dimensions:</b>	31" W x 48" L x 36.5" H
<b>Sold as:</b>	1 per package
<b>Absorbency:</b>	Up to 79.7 gal. per package
<b>Weight:</b>	203.78 lbs.
<b># per Pallet:</b>	1
<b>Incinerable:</b>	No
<b>Ship Class:</b>	200
<b>Includes:</b>	160 - 15" x 19" Gray Universal HeavyWeight SonicBonded Pads (GPB100H) 30 - 3" x 4' Gray Universal Sorbent Socks (GSO430) 10 - 3" x 8' Gray Universal Sorbent Socks (GSO815) 1 - Emergency Response GuideBook (A-EGB) 4 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISP BAG) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KIT LABEL) 1 - 48" x 31" x 38" Yellow Cart with 5" Rubber Wheels (A-UTILITYBOX5) 6 - 6" x 2" TamperProof Seals (A-SEAL) 4 - 25/pkg Wipers (WPR500-1)



### **Metric Equivalent Specifications**

<b>Dimensions:</b>	79cm W x 122cm L x 97cm H
<b>Shipping Dimensions:</b>	79cm W x 122cm L x 93cm H
<b>Absorbency:</b>	Up to 416 L per package
<b>Weight:</b>	93 kg

### **Regulations and Compliance:**

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."