



*Environmental*

**PH#: 941-747-4151**

**4455 18<sup>th</sup> St. East, Bradenton, FL 34203**

**barriers@aerflo.com**

## **MODEL 1D18P-36(PNEUMATIC) DRUM SKIMMER**

Line of drum skimmers are designed for both portability and extreme durability on the toughest jobs. Various 18" diameter oleophilic drums are capable of recovering hydrocarbons at rates of up to 35 gallons per minute. This easily deployable unit is ideal for inland and marsh spills, since it is capable of operating at water depths as shallow as 3".

Components of the **DRUM SKIMMER SYSTEMS** are detailed as follows:

- The **DRUM SKIMMER FLOTATION UNIT** is constructed of lightweight aluminum. Lifting handles and boom connector attachment points are provided. This pneumatically driven skimmer unit requires 0-100 psi @ 0-12 scfm air supply (available as option) to the FRL controller. Unit measures approximately 42" x 56" x 22" high and weighs approximately 95 pounds.
- The Pneumatically driven **Transfer Pump** (optional) is a double diaphragm pump (available as option) and is separate from the skimmer. This pump requires 125 psi @ 50 scfm air supply to the FRL controller.
- One set **Pump Suction and Discharge Hoses** (40' lengths) is available as optional.



**Recovery up to 35 gallons per minute.**  
(photo is representative)