



*Environmental*

**PH#: 941-747-4151**

**4455 18<sup>th</sup> St. East, Bradenton, FL 34203**

**barriers@aerflo.com**

## **Oil-Only Duffle Spill Kit - Absorbs up to 28.8 Gallons**

### **SPKO-DUFF Specifications**

<b>Dimensions:</b>	12" W x 40" L x 12" H
<b>Shipping</b>	15.75" W x 38" L x 13.25" H
<b>Dimensions:</b>	
<b>Sold as:</b>	1 per package
<b>Absorbency per:</b>	Up to 28.8 gal.
<b>Weight:</b>	26.65 lbs.
<b># per Pallet:</b>	18
<b>Incinerable:</b>	No
<b>Ship Class:</b>	175
<b>Includes:</b>	60 - 15" X 19" White Oil-Only HeavyWeight SonicBonded Pads (WPB100H) 8 - 3" x 4' White Oil-Only Sorbent Socks (WSO430) 2 - 18" x 18" White Oil-Only Sorbent Pillows (WPIL1818) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - Emergency Guide Book (A-EGB) 4 - 18" X 30" Yellow Disposal Bags & Ties (A-DISP BAG-SM) 1 - 40" x 12" x 12" Yellow Duffle Bag (A-DUFFLE) 2 - 7" Epoxy Stick (A-EPOXY)



### **Metric Equivalent Specifications**

<b>Dimensions:</b>	30cm W x 102cm L x 30cm H
<b>Shipping</b>	40cm W x 97cm L x 34cm H
<b>Dimensions:</b>	
<b>Absorbency per:</b>	Up to 109 L
<b>Weight:</b>	12.1 kg

### **Regulations and Compliance:**

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."