



Environmental

PH#: 941-747-4151

4455 18th St. East, Bradenton, FL 34203

barriers@aerflo.com

Universal Duffle Spill Kit - Absorbs up to 28.8 Gallons

SPKU-DUFF Specifications

Dimensions:	12" W x 40" L x 12" H
Shipping	15.75" W x 38" L x 13.25" H
Dimensions:	
Sold as:	1 per package
Absorbency per:	Up to 28.8 gal.
Weight:	26.65 lbs.
# per Pallet:	18
Incinerable:	No
Ship Class:	175
Includes:	60 - 15" x 19" Gray Universal HeavyWeight SonicBonded Pads (GPB100H) 8 - 3" X 4' Gray Universal Sorbent Socks (GSO430) 2 - 18" x 18" Gray Universal Sorbent Pillows (GPIL1818) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - Emergency Guide Book (A-EGB) 4 - 18" X 30" Yellow Disposal Bags & Ties (A-DISP BAG-SM) 1 - 40" x 12" x 12" Yellow Duffle Bag (A-DUFFLE) 2 - 7" Epoxy Stick (A-EPOXY)



Metric Equivalent Specifications

Dimensions:	30cm W x 102cm L x 30cm H
Shipping	40cm W x 97cm L x 34cm H
Dimensions:	
Absorbency per:	Up to 109 L
Weight:	12.1 kg

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."